

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.10.2021

Version number 4 (replaces version 3)

Revision: 12.05.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **EPOXY FAS 100 KOMP. A**

Article number: 0916

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC9a Coatings and paints, thinners, paint removers

Process category

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC10 Roller application or brushing

Environmental release category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

ERC8c Widespread use leading to inclusion into/onto article (indoor)

ERC11a Widespread use of articles with low release (indoor)

Application of the substance / the mixture Coating

Uses advised against No further relevant information available.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Remmers GmbH

Bernhard-Remmers-Str. 13

D-49624 Lönningen / Germany

Tel.: +49(0)5432/83-0

Fax: +49(0)5432/3985

Remmers (UK) Limited

Unit 4 , Lloyds Court

Manor Royal, Crawley – West Sussex RH10 9QU

fon +44 (0) 1293 594 010

fax +44 (0) 1293 594 037

Information department:

Product Safety department: Phone: +44 (0) 1293 594 010

Email: sales@remmers.co.ukk

1.4 Emergency telephone number:

National Poisons Information Service (NPIS):

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

24h-Transport Emergency Contact Phone Number:

within USA and Canada: 1-800-424-9300

outside USA and Canada: 001-703-527-3887

* SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.10.2021

Version number 4 (replaces version 3)

Revision: 12.05.2020

Trade name **EPOXY FAS 100 KOMP. A**

(Contd. of page 1)

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

GHS07 GHS09

Signal word Warning**Hazard statements**

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P262 Do not get in eyes, on skin, or on clothing.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****3.2 Mixtures****Description:** Mixture of the substances listed below with harmless additions.

Dangerous components [% w/w]:		
CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8 Reg.nr.: 01-2119456619-26-XXXX	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700) Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205 Specific concentration limits: Skin Irrit. 2; H315: C \geq 5 % Eye Irrit. 2; H319: C \geq 5 %	\geq 60-<80%
CAS: 28064-14-4 NLP: 500-006-8 Reg.nr.: 01-2119454392-40-XXXX	bisphenol F-(epichlorhydrin); epoxy resin(number average molecular weight<700) Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	\geq 10-<20%
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38-XXXX	benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	\geq 5-<10%
CAS: 2461-15-6 EINECS: 219-553-6 Reg.nr.: 01-2119962196-31-XXXX	[[[(2-ethylhexyl)oxy]methyl]oxirane Skin Irrit. 2, H315; Skin Sens. 1, H317	\geq 1-<2.5%

Additional information For the wording of the listed hazard phrases refer to section 16.

(Contd. on page 3)

Trade name **EPOXY FAS 100 KOMP. A**

(Contd. of page 2)

SECTION 4: First aid measures**4.1 Description of first aid measures****After inhalation**

Use a respiration bag or breathing device.

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

After skin contact

If skin irritation continues, consult a doctor.

Wash immediately with water and soap and rinse thoroughly.

After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

After swallowing Rinse out mouth and then drink plenty of water.**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing agents**

Water spray jet

Carbon dioxide

Foam

Use fire fighting measures that suit the environment.

5.2 Special hazards arising from the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:

Hydrogen chloride (HCl)

further harmful conflagration gases and fumes

5.3 Advice for firefighters**Protective equipment:** Wear self-contained breathing apparatus.**Additional information**

Cool endangered containers with water spray jet.

Collect contaminated fire fighting water separately. It must not enter drains.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation

6.2 Environmental precautions:

Do not allow to enter the ground/soil.

Do not allow product to reach sewage system or water bodies.

Inform responsible authorities in case product reaches bodies of water or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage**7.1 Precautions for safe handling** Use only in well ventilated areas.**Information about protection against explosions and fires:** No special requirements.**7.2 Conditions for safe storage, including any incompatibilities****Storage****Requirements to be met by storerooms and containers:** Prevent any penetration into the ground.**Information on storage in a common storage facility:**

Store away from oxidising agents.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.10.2021

Version number 4 (replaces version 3)

Revision: 12.05.2020

Trade name **EPOXY FAS 100 KOMP. A**

(Contd. of page 3)

Store away from food.

Further information about storage conditions:

Store container in a well ventilated position.

Protect from frost.

Keep container tightly closed.

7.3 Specific end use(s) No further relevant information available.**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Components with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with limit values that have to be monitored at the workplace.

Additional information: The lists that were valid during compilation were used as a basis.**8.2 Exposure controls****Appropriate engineering controls** No further data; see item 7.**Individual protection measures, such as personal protective equipment****General protective and hygienic measures**

Do not eat, drink or smoke while working.

Use skin protection cream for preventive skin protection.

Keep away from food, beverages and animal feed.

Immediately remove soiled, saturated clothing.

Wash hands before pauses and after work.

Avoid contact with eyes and skin.

Respiratory equipment:

In case of a risk of inhaling, wear half-mask with combination filter for organic vapours and particles.

Filter A/P2.

Only use ambient air independent respiratory equipment in pits, shafts and silos!

Hand protection

Long cuffed gloves

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection Tightly sealed safety glasses.**Body protection:** Protective work clothing.**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties****General Information**

Colour:	Clear
Odour:	Weak, characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Not determined
Boiling point or initial boiling point and boiling range	>100 °C
Flammability	Not applicable.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.10.2021

Version number 4 (replaces version 3)

Revision: 12.05.2020

Trade name **EPOXY FAS 100 KOMP. A**

(Contd. of page 4)

Lower and upper explosion limit	
Lower:	Not determined.
Upper:	Not determined.
Flash point:	>100 °C
Decomposition temperature:	Not determined.
pH	Not determined.
Viscosity:	
Kinematic viscosity	Not determined.
dynamic at 20 °C:	900-950 mPas
Solubility	
Water:	Not miscible or difficult to mix
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	
Density at 20 °C:	1.15-1.16 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of health and environment, and on safety.	
Ignition temperature:	not applicable
Explosive properties:	Product is not explosive.
Solvent separation test	< 3 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical hazard classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if handled and stored according to specifications.

10.3 Possibility of hazardous reactions Exothermic polymerisation

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products:

None if used properly.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.10.2021

Version number 4 (replaces version 3)

Revision: 12.05.2020

Trade name **EPOXY FAS 100 KOMP. A**

(Contd. of page 5)

None if stored properly.
 May be released in fire:
 Carbon monoxide and carbon dioxide
 Hydrogen chloride (HCl)
 Phenol

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity: Based on available data, the classification criteria are not met.

LD/LC50 values that are relevant for classification:

CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

Oral	LD50	>10,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)

Skin corrosion/irritation:

Causes skin irritation.

Serious eye damage/irritation:

Causes serious eye irritation.

Sensitisation:

May cause an allergic skin reaction.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure: Based on available data, the classification criteria are not met.

STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

12.7 Other adverse effects

Remark: Toxic for fish

Additional ecological information:

General notes:

Also toxic for fish and plankton in bodies of water.

Toxic for aquatic organisms

Do not allow product to reach ground water, bodies of water or sewage system.

Hazardous to drinking water even if small quantities leak into soil.

SECTION 13: Disposal considerations

Recommendation

Not hardened material must be disposed of as hazardous waste according to official regulations.

Hardened product remains may be disposed of as building rubble or put into household garbage.

The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.10.2021

Version number 4 (replaces version 3)



Revision: 12.05.2020

Trade name **EPOXY FAS 100 KOMP. A**

(Contd. of page 6)

European waste catalogue	
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Uncleaned packaging:**Recommendation:** Disposal must be made according to official regulations.**SECTION 14: Transport information**

14.1 UN number or ID number ADR, IMDG, IATA	UN3082
14.2 UN proper shipping name ADR	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin (reaction product: bisphenol A-(epichlorhydrin) (number average molecular weight \leq 700)))
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin (reaction product: bisphenol A-(epichlorhydrin) (number average molecular weight \leq 700))), MARINE POLLUTANT
IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin (reaction product: bisphenol A-(epichlorhydrin) (number average molecular weight \leq 700)))
14.3 Transport hazard class(es) ADR	
	
Class	9 (M6) Miscellaneous hazardous substances and articles.
Label	9
IMDG, IATA	
	
Class	9 Miscellaneous hazardous substances and articles.
Label	9
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	Product contains environmentally hazardous substances: Epoxy Resin (reaction product: bisphenol A-(epichlorhydrin) (number average molecular weight \leq 700))
Marine pollutant:	Yes
Special marking (ADR):	Symbol (fish and tree)
Special marking (IATA):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Miscellaneous hazardous substances and articles.
hazard identification number:	90
EMS Number:	F-A,S-F
Stowage Category	A

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.10.2021

Version number 4 (replaces version 3)

Revision: 12.05.2020

Trade name **EPOXY FAS 100 KOMP. A**

(Contd. of page 7)

14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	3
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN) (NUMBER AVERAGE MOLECULAR WEIGHT \leq 700))), 9, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category E2 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Delivery specifications are found in the respective Technical Information Sheets.

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship.

Relevant phrases

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H411 Toxic to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Classification according to Regulation (EC) No 1272/2008 Calculation method

Department issuing data specification sheet: Product Safety department / EHS

Version number of previous version: 3

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 11.10.2021

Version number 4 (replaces version 3)

Revision: 12.05.2020

Trade name EPOXY FAS 100 KOMP. A

(Contd. of page 8)

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2