



Partition Wall Strips

Closed-cell polyurethane foam for thermal, hygroscopic and acoustic decoupling in areas where walls and floors meet

Availability	
Quantity per pallet	300
Packaging unit	12 x
Type of container	Carton
Container code	01
Art. no.	
4258	■

Range of use

- Connecting joints between iQ Therm and neighbouring components, in particular where walls and floors meet
- For thermal, hygroscopic and acoustic decoupling
- For protecting components/building materials that are sensitive to moisture
- For preventing the transfer of moisture in the regions where iQ Therm meets other materials

Property profile

- Thickness: 3 mm
- Width: 75 mm
- Length per roll: 30 m

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.