



## Add TX

Organic thixotropic agent

Availability		
Quantity per pallet	150	40
Size / Quantity	1 kg	5 kg
Type of container	Paper bag	Paper bag
Container code	01	05
<b>Art. no.</b>		
0942	■	■

**Application rate** Depending on application and binder basis, approx. 1-10% by mass based on the binder

**Range of use** ■ Thixotropic agent for synthetic resins

**Property profile** ■ Easy to mix in

### Characteristic data of the product

Grain density	1.1 g/cm <sup>3</sup>
Form	Fibres

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

### Production of the mixture

Add according to the desired material properties of the A component and mix vigorously. Add a further quantity if necessary after adding the B component and mixing again.

### Directions

For professional users only!

Use, degree of filling and working directions are determined by the specific application and the resin/hardener system used.

### Notes

The amount of thixotropic agent used depends on the temperature of the material and air, and the method of incorporation.

Thixotropising influences the material properties.

Further notes on working, system construction and maintenance of the listed products can be found in the latest Technical Data Sheets and the Remmers system recommendations.



**Storage / Shelf life**

Unlimited if stored dry.



**Safety data / Regulations**

For professional users only!

Further information concerning safety during transport, storage and handling as well as on disposal and ecology can be found in the latest Safety Data Sheet.

**Personal protective equipment**

This information can be obtained from the current Safety Data Sheets and/or the relevant professional associations.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.